


Hauptmerkmale


- Werkstoff PA 6.6
- -40°C - 85°C
- halogenfrei
- schwer entflammbar
- in schwarz, natur, weitere Farben auf Anfrage



lösbare Kabelbinder

Teile-Nummer Packung		Länge	Breite	Bündel-Ø max.	Zugfestigkeit
1000	100	mm	mm	mm	kg
-	GTR-140IC	140	3.6	33	18,2
-	GTR-200STC	200	4.8	50	22,2
-	GTR-300STC	300	4.8	86	22,2
-	GTR-370STC	370	4.8	102	22,2
-	GTRN-120HDC	120		30	
-	GTRN-150HDC	150		35	
-	GTRN-200HDC	200	7.6	50	22,2
-	GTRN-250HDC	250		66	
-	GTRN-300HDC	300		80	

Ösenbinder

GTM-110M	GTM-110MC	110	2.5	22	81			
GTM-150I	GTM-150IC	150	3.6	32	182			
GTM-200ST	GTM-200STC	200	4.8	50	222			
GTM-300ST	GTM-300STC	310	4.8	76	222			
-	GTM-200HDC	200	7.6	50	544	Binder- Breite	Befest.öse	Schraube
-	GTM-300HDC	313	7.6	76	544	2,5	3,2mm	M3
						3,6	4,5mm	M4
						4,8	5,5mm	M5
						7,6	6,3mm	M6