

Hauptmerkmale

- Werkstoff PA 6.6
- -40°C + 85°C
- halogenfrei
- schwer entflammbar
- in schwarz, natur, weitere Farben auf Anfrage



Artikelbezeichnung Packung/Pkg		Länge	Breite	Bündel-Ø max.	Zugfestigkeit
1000	100	mm	mm	mm	kg/daN
GT-100M	GT-100MC	100	2,5	24	11
GT-120M	-	120	2,5	30	11
GT-135M	GT-135MC	135	2,5	35	11
GT-160M	GT-160MC	160	2,5	42	11
GT-200M	GT-200MC	200	2,5	55	11
GT-140I	GT-140IC	140	3,6	33	18
GT-150I	GT-150IC	150	3,6	37	18
GT-200I	GT-200IC	200	3,5	55	20
-	GT-225IC	225	3,5	65	20
-	GT-250IC	250	3,5	70	20
-	GT-280IC	280	3,5	80	20
GT-300I	GT-300IC	300	3,6	76	18
-	GT-360IC	360	3,5	103	20
GT-140ST	GT-140STC	140	4,5	33	28
GT-160ST	GT-160STC	160	4,5	38	28
GT-180ST	GT-190STC	180	4,5	45	28
GT-200ST	GT-200STC	200	4,5	51	28
-	GT-250STC	250	4,5	68	28
	GT-300STC	280	4,5	76	28
-	GT-301STC	300	4,5	80	28
-	GT-370STC	360	4,5	101	28
-	GT-380STC	380	4,5	110	28
-	GT-430STC	430	4,5	123	28
-	GT-360HDC	360	6,0	101	45

Artikelbezeichnung Packung/Pkg		Länge	Breite	Bündel-Ø max.	Zugfestigkeit
1000	100	mm	mm	mm	kg/daN
-	GT-180HDC	180	7,5	44	65
-	GT-200HDC	200	7,5	48	65
-	GT-240HDC	240	7,5	62	65
-	GT-280HDC	280	7,5	76	65
-	GT-300HDC	320	7,5	88	65
-	GT-320HDC	320	7,5	88	65
-	GT-360HDC	360	7,5	101	65
-	GT-370HDC	370	7,6	102	65
-	GT-450HDC	450	7,5	130	65
-	GT-500HDC	500	7,5	145	65
-	GT-540HDC	540	7,5	160	65
-	GT-750HDC	750	7,5	222	65